

GSTIN : 22AUFP8634F1Z1

AMAR JYOTI

MACHINERY CORPORATION



4, MAIN BILASPUR ROAD, BHANPURI CHOWK, BHANPURI, RAIPUR-493221, CHHATTISGARH (IND)

Mo.: +91-9522015586; +91-9522015584

INDUSTRIAL MACHINERY

Visit At: WWW.AMARJYOTIMACHINERY.COM Email : raipur.amarjyoti@gmail.com

AMAR JYOTI MACHINERY



MECHANICAL/PNEUMATIC PRESS BRAKE

1270 x 2 mm to 3150 x 8 mm
20 Ton to 200 Ton

MECHANICAL / PNEUMATIC
PRESS BRAKE

Mechanical/Pneumatic Press Brake Specification

MODEL	TONNAGE	BENDING CAP. IN MS LENGTH x THICKNESS	CLEAR DISTANCE BETWEEN HOUSINGS	MAIN MOTOR HP / KW	RAM ADJ. ELE. MOTOR HP / KW	STROKE PER MINUTE	STROKE OF RAM M.M.	RAM ADJ. M.M.	SHUT HEIGHT RAM STROKE	DEPTH OF THROAT MM	OVERALL DIMENSION IN MM (APP)		
											LENGTH A	WIDTH B	HEIGHT C
PB-01	20	1525 x 1.6	1000	3 / 2.2	MANUAL	30	50	40	200	200	1900	1100	2300
PB-02	30	2030 x 2	1220	5 / 3.7	05/	30	60	40	200	200	2400	1100	2300
PB-03	30	2540 x 1.6	1700	5 / 3.7	1 / .75	30	60	40	200	200	2900	1100	2300
PB-04	40	1525 x 3	1000	7.5 / 5.6	05/	30	60	40	200	200	1900	1200	2300
PB-05	40	1540 x 2	1700	7.5 / 5.6	1 / .75	30	60	40	200	200	2900	1200	2300
PB-06	60	2030 x 4	1220	7.5 / 5.6	1 / .75	30	60	50	225	225	2400	1200	2500
PB-07	60	2540 x3	1700	7.5 / 5.6	1 / .75	30	60	50	225	225	2900	1200	2500
PB-08	80	2030 x 5	1220	10 / 7.7	1 / .75	25	75	75	250	250	2400	1500	2800
PB-09	80	2540 x 4	1700	10 / 7.7	1 / .75	25	75	75	250	250	2900	1500	2800
PB-10	80	3125 x 3	1900	10 / 7.7	1 / .75	25	75	75	250	250	3500	1500	2800
PB-11	100	2030 x 6	1220	12.5 / 9.7	1.5 / 1	25	75	75	290	250	2400	1800	3000
PB-12	100	2540 x 5	1700	15 / 11.2	1.5 / 1	25	75	75	250	250	2900	1800	3000
PB-13	100	3125 x 4	1900	15 / 11.2	1.5 / 1	25	75	75	250	250	3500	1800	3000
PB-14	120	2030 x8	1220	15 / 11.2	2 / 1.5	20	75	75	275	300	2500	1800	3400
PB-15	120	2540 x 6	1700	15 / 11.2	2 / 1.5	20	75	75	275	300	3000	1800	3400
PB-16	120	3125 x 5	1900	15 / 11.2	2 / 1.5	20	75	75	275	300	3700	1800	3400
PB-17	160	2030 x 10	1220	20 / 15	2 / 1.5	20	75	90	300	300	2500	2000	3400
PB-18	160	2540 x 8	1700	20 / 15	2 / 1.5	20	75	90	300	300	3100	2000	3400
PB-19	160	3125 x 6	1900	20 / 15	2 / 1.5	20	75	90	300	300	3700	2000	3400
PB-20	200	2030 x12	1220	25 / 18.7	2 / 1.5	20	90	90	300	300	2500	2100	3600
PB-21	200	2540 x 10	1700	25 / 18.7	2 / 1.5	20	90	90	300	300	3100	2100	3600
PB-22	200	3125 x 8	1900	25 / 18.7	2 / 1.5	20	90	90	300	300	3700	2100	3600

SUPPLY: 400/440 Volts, 3 Phase, 50 Cycles, All dimensions are in mm

NOTE: Electricals & Blades are not under Warranty.

Specification / Design are Subject to change without prior notice



C TYPE POWER PRESS



H TYPE POWER PRESS



PNEUMATIC POWER PRESS



MECHANICAL UNDER CRANK SHEARING
610 x 1 mm to 3125 x A mm



MECHANICAL/PNEUMATIC PRESS BRAKE
610 x 1 mm to 3125 x A mm



HYDRAULIC SHEARING
1500 x 3 mm to 8000 x 25 mm