

GSTIN : 22AUFPA8634F1Z1

AMAR JYOTI

MACHINERY CORPORATION



4, MAIN BILASPUR ROAD, BHANPURI CHOWK, BHANPURI, RAIPUR-493221, CHHATTISGARH (IND)
Mo.: +91-9522015586; +91-9522015584

INDUSTRIAL MACHINERY

Visit At: WWW.AMARJYOTIMACHINERY.COM Email : raipur.amarjyoti@gmail.com

AMAR JYOTI MACHINERY



REAR CYLINDER HYDRAULIC PRESS BRAKE

1270 x 2 mm to 8000 x 8 mm
20 Ton to 1000 Ton

REAR CYLINDER
HYDRAULIC PRESS BRAKE

Rear Cylinder Hydraulic Press Brake Specification

MODEL	TONNAGE	BENDING CAP IN MS LENGTH x THICKNESS	TABLE WIDTH	CLEAR DISTANCE	RAM STROKE	OPEN HEIGHT	DEPTH	POWER H.P.	SPEED AAP. PRE. RET.	PACKING DIMENSION IN MM		
										LENGTH A	WIDTH B	HEIGHT C
PBR-212	20	1270 x 2.5	150	900	100	250	200	3	35-9-60	1400	1050	1900
PBR-215	20	1525 x 2	150	1100	100	250	200	3	35-9-60	1700	1050	1900
PBR-312	30	1270 x 3	150	900	100	250	200	3	30-9-53	1400	1050	1900
PBR-315	30	1525 x 2.15	150	1100	100	250	200	3	30-9-53	2700	1050	1900
PBR-320	30	2030 x 2	150	1500	100	250	200	3	30-9-53	2200	1050	1900
PBR-325	30	2540 x 1.6	150	2000	100	250	200	3	30-9-53	2700	1050	1900
PBR-412	40	1270 x 4	150	900	100	250	200	5	35-9-55	1400	1050	1900
PBR-415	40	1525 x 3	150	1100	100	250	200	5	35-9-55	1700	1050	1900
PBR-420	40	2030 x 2.5	150	1550	100	250	200	5	35-9-55	2200	1050	1900
PBR-425	40	2540 x 2	150	2000	100	250	200	5	35-9-55	2700	1050	1900
PBR-430	40	3125 x 1.6	150	2500	400	250	200	5	35-9-55	3300	1050	1900
PBR-512	50	1270 x 5	175	900	125	250	200	5	30-7-55	1400	1050	1900
PBR-515	50	1525 x 4	175	1100	125	250	200	5	30-7-55	1700	1050	1900
PBR-520	50	2030 x 3	175	1550	125	250	200	5	30-7-55	2200	1050	1900
PBR-525	50	2540 x 2.5	175	2000	125	250	200	5	30-7-55	2700	1050	1900
PBR-530	50	3125 x 2	175	2500	125	250	200	5	30-7-55	3300	1050	1900
PBR-612	60	1270 x 6	175	900	125	330	200	5	25-6-50	1400	1200	2000
PBR-615	60	1525 x 5	175	1100	125	330	200	5	25-6-50	1700	1200	2000
PBR-620	60	2030 x 4	175	1550	125	330	200	5	25-6-50	2200	1200	2000
PBR-625	60	2540 x 3	175	2000	125	330	200	5	25-6-50	2700	1200	2000
PBR-630	60	3125 x 2.5	175	2500	125	330	200	5	25-6-50	3300	1200	2000
PBR-812	80	1270 x 8	200	400	150	330	200	7.5	37-6-41	1400	1500	2200
PBR-815	80	1525 x 6	200	1100	150	330	250	7.5	37-6-41	1700	1500	2200
PBR-820	80	2030 x 5	200	1550	150	330	250	7.5	37-6-41	2200	1500	2200
PBR-825	80	2540 x 4	200	2000	150	330	250	7.5	37-6-41	2700	1500	2200
PBR-830	80	3125 x 3	200	2500	150	330	250	7.5	37-6-41	3300	1500	2200
PBR-840	80	4000 x 2.5	200	3500	150	330	250	7.5	37-6-41	4200	1500	2200
PBR-1012	100	1270 x 10	200	900	150	330	250	7.5	40-5-40	1400	1500	2200
PBR-1015	100	1525 x 8	200	1100	150	330	250	7.5	40-5-40	1700	1500	2200
PBR-1020	100	2030 x 6	200	1550	150	330	250	10	40-5-40	2200	1600	2300
PBR-1025	100	2540 x 5	200	2000	150	330	250	10	40-5-40	2700	1600	2300
PBR-1030	100	3125 x 4	200	2500	150	330	250	10	40-5-40	3300	1600	2300
PBR-1040	100	4000 x 3	200	3000	150	330	250	10	40-5-40	4200	1600	2300
PBR-1050	100	5000 x 2.5	200	4000	150	330	250	10	40-5-40	5200	1600	2300
PBR-1060	100	6000 x 2	200	5000	150	330	250	10	40-5-40	6200	1600	2300
PBR-1212	120	1270 x 12	225	900	150	330	300	10	41-6-41	1400	1700	2300
PBR-1215	120	1525 x 10	225	1100	150	330	300	10	41-6-41	1700	1700	2500
PBR-1220	120	2030 x 8	200	1550	150	330	300	10	41-6-41	2200	1700	2800
PBR-1225	120	2540 x 6	200	2000	150	330	300	10	41-6-41	2700	1700	2500
PBR-1230	120	3125 x 5	200	2500	150	330	300	10	41-6-41	3300	1700	2500
PBR-1240	120	4000 x 4	200	3000	150	330	300	10	41-6-41	4200	1700	2500
PBR-1250	120	5000 x 3	150	4000	150	330	300	10	41-6-41	5200	1700	2500
PBR-1260	120	6000 x 2.5	150	5000	150	330	300	10	41-6-41	6200	1700	2500
PBR-1612	160	1270 x 16	225	900	200	375	300	15	40-6-40	1400	1800	2500
PBR-1615	160	1525 x 12	225	1100	200	375	300	15	40-6-40	1700	1800	2500
PBR-1620	160	2030 x 10	225	1550	200	375	300	15	40-6-40	2200	1800	2500
PBR-1625	160	2540 x 8	200	2000	200	375	300	15	40-6-40	2700	1800	2500
PBR-1630	160	3125 x 6	200	2500	200	375	300	15	40-6-40	3300	1800	2500
PBR-1640	160	4000 x 5	200	3000	200	375	300	15	40-6-40	4200	1800	2500
PBR-1650	160	5000 x 4	175	4000	200	375	300	15	40-6-40	5200	1800	2500

Rear Cylinder Hydraulic Press Brake Specification

MODEL	TONNAGE	BENDING CAP. IN MS LENGTH x THICKNESS	TABLE WIDTH	CLEAR DISTANCE	RAM STROKE	OPEN HEIGHT	DEPTH	POWER H.P.	SPEED AAP. PRE. RET.	PACKING DIMENSION IN MM		
										LENGTH A	WIDTH B	HEIGHT C
PBR-1660	160	6000 x 3	175	5000	200	375	300	15	40-6-40	6200	1800	2500
PBR-2020	200	2030 x 12	250	1550	200	375	300	20	37-5-37	2200	2000	2600
PBR-2025	200	2540x10	250	2000	200	375	300	20	37-5-37	2700	2000	2600
PBR-2030	200	3125 x 8	250	2500	200	375	300	20	37-5-37	3300	2000	2600
PBR-2040	200	4000 x 6	200	3000	200	375	300	20	37-5-37	4200	2000	2600
PBR-2050	200	5000 x 5	200	4000	200	375	300	20	37-5-37	5200	2000	2600
PBR-2060	200	6000 x 4	200	5000	200	375	300	20	37-5-37	6200	2000	2600
PBR-2520	250	2030 x 16	300	1550	200	375	300	25	40-5-40	2200	2100	2700
PBR-2525	250	2540 x 13	300	2000	200	375	300	25	40-5-40	2700	2100	2200
PBR-2530	250	3125 x 10	250	2500	200	375	300	25	40-5-40	2300	2100	2700
PBR-2540	250	4000 x 8	200	3000	200	375	300	25	40-5-40	4200	2100	2700
PBR-2550	250	5000 x 6	200	4000	200	375	300	25	40-5-40	5200	2100	2700
PBR-2560	250	6000 x 5	200	5000	200	375	300	25	40-5-40	6200	2100	2700
PBR-3020	300	2030 x 20	275	1550	200	425	300	30	36-5-36	2200	2150	2900
PBR-3025	300	2540 x 16	275	2000	200	425	300	30	36-5-36	2700	2150	2900
PBR-3030	300	3125 x 13	275	2500	200	425	300	30	36-5-36	3300	2150	2900
PBR-3040	300	4000 x 10	275	3000	200	425	300	30	36-5-36	4200	2150	2900
PBR-3050	300	5000 x 8	250	4000	200	425	300	30	36-5-36	5200	2150	2900
PBR-3060	300	6000 x 6	250	5000	250	425	300	30	36-5-36	6200	2150	2900
PBR-4020	400	2030 x 25	400	1550	250	450	350	40	34-5-34	2200	2200	3000
PBR-4025	400	2540 x 20	400	2000	250	450	350	40	34-5-34	2700	2200	3000
PBR-4030	400	3125 x 16	300	2500	250	450	350	40	34-5-34	3300	2200	3000
PBR-4040	400	4000 x 13	300	3000	250	450	350	40	34-5-34	4200	2200	3000
PBR-4050	400	5000 x 10	300	4000	250	450	350	40	34-5-34	5200	2200	3000
PBR-4060	400	6000 x 8	350	5000	250	450	350	40	34-5-34	6200	2200	3000
PBR-5020	500	2030 x 30	400	1550	250	450	350	50	28-5-28	2200	2300	3200
PBR-5025	500	2540 x 25	400	2000	250	450	400	50	28-5-28	2700	2300	3200
PBR-5030	500	3125 x 20	400	2500	250	450	400	50	28-5-28	3300	2300	3200
PBR-5040	500	4000 x 16	300	3000	250	450	400	50	28-5-28	4200	2300	3200
PBR-5050	500	5000 x 13	300	4000	250	450	400	50	28-5-28	5200	2300	3200
PBR-5060	500	6000 x 10	300	5000	250	450	400	50	28-5-28	6200	2300	3200

SUPPLY: 400/440 Volts, 3 Phase, 50 Cycles, All dimensions are in mm

NOTE: Electricals & Blades are not under Warranty.

Specification / Design are Subject to change without prior notice



'C' TYPE POWER PRESS



'H' TYPE POWER PRESS



PNEUMATIC POWER PRESS



MECHANICAL UNDER CRANK SHEARING
610 x 1 mm to 3125 x A mm



MECHANICAL/PNEUMATIC PRESS BRAKE
610 x 1 mm to 3125 x A mm



HYDRAULIC SHEARING
1500 x 3 mm to 8000 x 25 mm